Smart Dongle-4G



Smart

2G, 3G, 4G communication[1]
Support 3rd-party monitoring system[2]

Simple

Plug & Play
Support max. 10 devices

Reliable

IP65
Support auto reconnection

Technical Specification	SDongleA-03-EU
General Data	
Max. Devices Supported	10
Max. Inverters Supported	10
Connection interface	USB
Installation	Plug-and-play
Indicator	LED Indicator
Dimensions (W * H * D)	130 x 48 x 33 mm (5.1 x 1.9 x 1.3 inch)
Weight	90 g (0.2 lb.)
Degree of protection	IP65
Power consumption (typical)	3.5 W
Wireless Parameter	
Sim card type	mini-sim (15 mm*25 mm)
Supported standards & frequencies	4G: FDD-LTE / TDD-LTE 3G: WCDMA / HSDPA / HSUPA / HSPA+ 2G: GSM / GPRS / EDGE [3]
Environment	
Operating temperature range	-30 ℃ to +65 ℃ (-22 ℉ to 149 ℉)
Relative humidity range	5 - 95% RH
Storage temperature range	-40 ℃ to +70 ℃ (-40 ℉ to 158 ℉)
Max. operating altitude	4,000 m (13,123 ft.)
Standard Compliance (more available upon request)	
Certificate	CE, Type Approval for Thailand, MIC
Inverter Compatibility	
Inverter model	SUN2000-2/3/3.68/4/4.6/5/6KTL-L1 SUN2000-3/4/5/6/8/10KTL-M0/M1 SUN2000-12/15/17/20KTL-M0/M2 SUN2000-60KTL-M0 SUN2000-100KTL-M1

1: To ensure stable data transmission, Huawei suggests 4G dongle to be installed in areas with stable mobile signal (2G signal ≥4 bars, 3G/4G signal ≥3 bars). 2: 3rd-party management system shall match the communication protocol with Huawei Smart Dongle.
3. For recommended carriers list and details on supported frequencies, pleasecontact local distributors.