

MONOCRYSTALLINE MODULE

DM285-M156-60 Series

60 x 6" / 265 - 285W

Wattages:

265 / 270 / 275

280 / 285



Technology

High module conversion efficiency through superior manufacturing technology



PID Free



Power-Positive Tolerance

Guaranteed power output (0/+3%)



Performance

High performance under low light conditions (Cloudy days, mornings and evenings)



Quality

Manufactured according to International Quality and Environmental Management Systems (ISO9001, ISO14001)




Value

Our vertically integrated business model allows for competitive pricing and great value

www.dmegcsolar.com

Excellent Electrical Performance Cells



- PERC Monocrystalline 156.75X156.75mm cells have been used in the modules with better performance in terms of parameters

Visible Quality



- Durable, high-quality, smooth aluminum alloy frames
- Rigid construction - 2400 Pa 5400 Pa rated assembly
- Specially designed drainage holes prevent the frame from deforming or breaking due to freezing weather and other forces

Warranty

- 10 Year Manufacturer's Warranty
 - 10 Year Warranty, 90% power output
 - 25 Year Warranty, 80% power output
- Certifications and standards:
IEC 61215, IEC 61730
-Conformity to CE UL1703

Superior Manufacturing - Quality Assurance



- All modules are manufactured using TQC & SPC quality control systems
- Advanced cell sorting to avoid electric mismatch
- 100% EL Test- before lamination & prior to shipment
- Comprehensive safety and reliability tests are performed

Power Output



- Our IP67 rated junction box improves module performance and stability
- High-performance connectors provide low resistance interconnection to ensure the full utilization of module output power

