

THE Honey MODULE

TSM-PD05



60 CELL

MULTICRYSTALLINE MODULE

255–265W

POWER OUTPUT RANGE

16.2%

MAXIMUM EFFICIENCY

0/+5W

POSITIVE POWER TOLERANCE

TRINA SOLAR: A STRONG AND RELIABLE PARTNER

As a leading global manufacturer of next generation photovoltaic products, Trina Solar is committed to building mutually beneficial alliances with installers, developers, distributors and technological partners as the backbone of our shared goal to drive Smart Energy Together. Thanks to an extensive sales and service network with local expert teams throughout Europe, Trina Solar is perfectly positioned to support your needs. With Trina Solar as your strong, bankable partner you can rest assured knowing that you've made the right choice.

www.trinasolar.com



Excellent low light performance on cloudy days, mornings and evenings

- Advanced surface texturing
- Back surface field
- Selective emitter



Maximize Limited Space

- 60-cell module power output up to 265W
- Up to 162 W/m² power density



Highly reliable due to stringent quality control

- All modules have to pass electroluminescence (EL) inspection
- Over 30 in-house tests (UV, TC, HF, and many more)
- In-house testing goes well beyond certification requirements
- PID resistant
- 1000 V UL/1000 V IEC certified




Certified to withstand challenging environmental conditions



- 130 km/h wind load (2400 Pa)
- 900 kg snow load per module (5400 Pa)
- 35 mm hail stones at 97 km/h
- Ammonia resistance
- Salt mist resistance
- resistance to sand and dust abrasion

LINEAR PERFORMANCE WARRANTY


10 Year Product Warranty • 25 Year Linear Power Warranty



DIMENSIONS OF PV MODULE TSM-PD05
(unit:mm)



I-V CURVES OF PV MODULE TSM-260 PD05



CERTIFICATION

IEC 61215/EN61215
IEC 61730/EN61730
IEC 627162 PtG 1917/05.11*
IEC 61701*
DIN EN 60068-2-68 LC2*
MCS BRE PV0183*



ELECTRICAL DATA @ STC

	TSM-255 PD05	TSM-260 PD05	TSM-265 PD05
Peak Power Watts- P_{MAX} (Wp)	255	260	265
Power Output Tolerance- P_{MAX} (W)	0/+5	0/+5	0/+5
Maximum Power Voltage- V_{MPP} (V)	30.5	30.6	30.8
Maximum Power Current- I_{MPP} (A)	8.37	8.50	8.61
Open Circuit Voltage- V_{OC} (V)	38.1	38.2	38.3
Short Circuit Current- I_{SC} (A)	8.88	9.00	9.10
Module Efficiency η_m (%)	15.6	15.9	16.2

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5

ELECTRICAL DATA @ NOCT

	TSM-255 PD05	TSM-260 PD05	TSM-265 PD05
Maximum Power- P_{MAX} (Wp)	189	193	197
Maximum Power Voltage- U_{MPP} (V)	28.2	28.4	28.6
Maximum Power Current- I_{MPP} (A)	6.71	6.81	6.89
Open Circuit Voltage- U_{OC} (V)	35.3	35.4	35.5
Short Circuit Current- I_{SC} (A)	7.17	7.27	7.35

NOCT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar Cells	Multicrystalline 156 x 156 mm
Cell Orientation	60 cells (6 x 10)
Module Dimensions	1650 x 992 x 35 mm
Weight	18.6 kg
Glass	High Transparency, Anti-Reflective, AR Coated and Heat Tempered Solar Glass - 3.2mm
Backsheet	White
Frame	Silver Anodized Aluminium Alloy
J-Box	IP 65 or IP 67 rated
Cables	Photovoltaic Technology Cable 4.0 mm², 1000 mm
Connector	MC4 Compatible

TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	44°C (±2K)
Temperature Coefficient of P_{MAX}	- 0.41%/K
Temperature Coefficient of V_{OC}	- 0.32%/K
Temperature Coefficient of I_{SC}	0.05%/K

MAXIMUM RATINGS

Operational Temperature	-40 to +85°C
Maximum System Voltage	1000V DC (IEC) 1000V DC (UL)
Max Series Fuse Rating	15 A
Mechanical Load	5400 Pa
Wind Load	2400 Pa

WARRANTY

10 year Product Workmanship Warranty
25 year Linear Performance Warranty

(Please refer to product warranty for details)

PACKAGING CONFIGURATION

Modules per box: 30 pieces
Modules per 40' container: 840 pieces



TSM_EN_2016_A

*being updated